LOFT WALL LIGHT



FITTING INFORMATION

Arm

Material: Aluminium

Colour: Flat Black Or Flat White Powder Coat

Size : L705 x W95 x H260mm

Cleaning : Damp cloth with mild detergent

Collar: Solid brass collar with thumb screw or Satin Nickel

Collar with thumb screw

Shield

Material: Aluminium

Finishes: Brushed Gold (Flat Black Loft)

Flat White Powder Coat (Flat White Loft)

Size: Ø42 x H88mm

Cleaning: Damp cloth with mild detergent

Wall Bracket

Material: Mild Stee

Colour: Flat Black or Flat White powder coat

Size: L80 x W30 x H100mm

Wall mount

footprint: W30 x H100mm

Mounting: 2 x M4 screws, 50mm centre to centre

Hardwired canopy

mounting footprint: Ø80mm

Application

Indoor (IP20)

TECHNICAL DATA

Lamp

Retrofit LED filament clear G95 spherical lamp, ES base

Switching & Dimming

Switching: Cordline switch with plug or

Hardwired to power supply, wall switched

— Flat Black Canopy (Flat Black Loft)

— Flat White Canopy (Flat White Loft)

Dimming: Subject to lamp compatability


.IES & .RFA files upon request

ORDER INFO


Product range - Model number - Finish/Colour

	Cordline Switch and Plug	Hard wired with Wall canopy
Flat Black/Brass coupling/Brushed Gold Anodised cylinder	LO-W03-115	LO-W04-115
Flat White/Brass coupling/Brushed Gold Anodised cylinder	LO-W07-115	LO-W08-115

DIMENSIONAL DRAWING



PHOTOMETRIC DATA







LOFT

Steel wall bracket and aluminium stem in choice of flat black powder coat, brushed gold anodised cylinder and brass coupling or flat white powder coat, brushed silver anodised cylinder and satin nickel coupling.

